

WHAT IS CLAIMED IS:

1. A retainer comprising:

a pin adapted for attachment to a mounting member for supporting a stack of sheets having one or more openings; said pin comprising a shank portion for insertion into the one opening, an outer end portion defining a pair of parallel bores with transversely spaced apart axes, and an inner end portion attachable to the support member; and

a spring clamp comprising a pair of leg portions having outer end portions joined by a yoke portion and inner ends each joined to a journal portion received by a different one of said bores.

2. An apparatus according to claim 1 wherein said outer end portion is displaced a substantial distance d from said inner end portion.

3. An apparatus according to claim 2 wherein said distance d is substantially greater than a maximum width W of said pin.

4. An apparatus according to claim 1 wherein said leg portions are non-parallel and have equal lengths.

5. An apparatus according to claim 4 wherein said bores lie in a plane oriented obtusely to the stack of sheets.

6. An apparatus according to claim 1 wherein said pin is cylindrical and said outer end defines a pair of substantially planar, parallel surfaces penetrated by said bores.

7. An apparatus according to claim 6 wherein said shank portion has outer beveled surface portions intersecting said parallel surfaces.

8. An apparatus according to claim 7 wherein a tip of said outer end portion is inwardly tapered.

9. An apparatus according to claim 8 wherein said shank portion and said inner end portion define an axial threaded bore.

10. An apparatus according to claim 1 wherein said leg portions are substantially parallel and said yoke portion is elongated and projects transversely from said leg portions.

11. An apparatus according to claim 3 wherein said leg portions are substantially parallel and said yoke portion is elongated and projects transversely from said leg portions.

12. An apparatus according to claim 11 wherein said bores lie in a plane oriented obtusely to the stack of sheets.

13. An apparatus according to claim 12 wherein said pin is cylindrical and said outer end defines a pair of substantially planar, parallel surfaces penetrated by said bores.

14. An apparatus according to claim 13 wherein said shank portion has outer beveled surface portions intersecting said parallel surfaces.

15. An apparatus according to claim 14 wherein a tip of said outer end portion is inwardly tapered.

16. An apparatus according to claim 15 wherein said shank portion and said inner end portion define an axial threaded bore.

17. An apparatus according to claim 16 wherein said leg portions are non-parallel and have equal lengths.

18. An apparatus according to claim 8 wherein said outer end portion is displaced a substantial distance d from said inner end portion.

19. An apparatus according to claim 18 wherein said distance d is substantially greater than a maximum width W of said pin.

20. An apparatus according to claim 19 wherein said bores lie in a plane oriented obtusely to the stack of sheets.